



Pro 3

Abrasion

Approx. 80.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 4, EN ISO 12945

Seam slippage

Seam parallel to warp: 4.0 mm parallel to weft: 3.5 mm
EN ISO 13 936-2 180 Newton

Lightfastness

Note 6-7 ISO 105-B02

Fastness to rubbing

Dry note 5 ISO 105-X12
Wet note 4-5 ISO 105-X12

Absorption

0.60/Class C (flat), 0.80/Class B (waved) EN ISO 354

Airflow

974 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3
AS/NZS 3837 class 1
ASTM E84 Class A Unadhered
BS 5852 Crib 5
DIN 4102 B1
EN 1021-1/2
EN 13501-1, B-s1, d0
FAR 25.853
GB 8624 B1
IMO FTP Code 2010 Part 7
IMO FTP Code 2010 Part 8
NF D 60 013
NF P 92 507 M1
NFPA 701
ÖNORM B1/Q1
SN 198 898 5.2
UNI 9175 1IM
UNI 9177 Classe 1
US Cal. Bull. 117-2013

Pro 3

Design: Finn Sködt

Type: Upholstery

In accordance with California AB2998 or similar regulation in other states of North America, this product should not be used for upholstery in USA

Composition: 100% Trevira CS

Yarn type: Filament

Binding: Panama

Width: Approx. 150 cm, 59 inches

Weight: Approx. 510 g/lin.m, 16.5 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week if fixed covers. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.


Also washable at 60-80°C, half wash load. Drip drying.

Mount in moist condition. Shrinkage app. 2% at 60°C.

Be aware of increased shrinking and creasing the higher the temperature.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year
warranty



kvadrat

ACT Guidelines Woven fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Colour Fastness to Light

Grade 5.0 minimum 40 hours

Physical properties

Pilling Class 4

Breaking Strength warp 286 / weft 296 lbs.

Seam Slippage warp 119.5 / weft 120 lbs.

Abrasion

80.000 cycles Martindale – High Traffic / Public Spaces

Quality benefits

Complies with Möbelfakta

Very good abrasion

Very good lightfastness

Permanent flame retardant

Washable

Environmental benefits

EU Ecolabel compliant

No use of halogen-based flame retardants (incl. brominated and chlorinated)

No content of PFCs or 'PFAS'

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono-material designed for circularity

Recyclable

Green building certificates

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): Based on a LCA following EN 15804 and follow the standard of ISO 14040

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Holland

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information
kvadrat.dk

kvadrat