



## Savanna

### Abrasion

Approx. 45.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

### Pilling

Note 3, EN ISO 12945

### Seam slippage

Seam parallel to warp: 2.5 mm parallel to weft: 6.5 mm  
EN ISO 13 936-2 180 Newton

### Snagging

Note 1-2 (Note 1-4, 1 best note) ICI Test method FAB 29, Tumble-Box

### Lightfastness

Note 5-7 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 4-5 ISO 105-X12

### Flame resistance

AS/NZS 3837 class 2  
BS 5852 crib 5 with treatment \*  
BS 5852 part 1 with treatment \*  
EN 1021-1/2  
NF D 60 013 with treatment \*  
SN 198 898 5.3 with treatment \*  
UNI 9175 1IM with treatment \*  
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

### Savanna

Design: Aggebo & Henriksen

Type: Upholstery

Composition: 34% polyester, 31% new wool, 26% polyacrylic, 4% cotton, 3% nylon, 2% linen

Yarn type: Spun

Binding: Dobby

Width: Approx. 140 cm, 55 inches

Weight: Approx. 681 g/lin.m, 22 oz/ly

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year  
warranty



# kvadrat

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking**

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

### **Colour Fastness to Light**

Grade 5.0 minimum 40 hours

### **Physical properties**

Pilling Class 3

Breaking Strength warp 161 / weft 200 lbs.

Seam Slippage warp 25 / weft 89 lbs.

### **Abrasion**

45.000 cycles Martindale – High Traffic / Public Spaces

### **Benefits of wool**

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/  
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

### **Quality benefits**

Very good abrasion

Very good lightfastness

Flame retardant

### **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No content of PFCs or 'PFAS'

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

### **Green building certificates**

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): Based on a LCA following EN 15804 and follow the standard of ISO 14040

Health Product Declaration (HPD): Declaring textile content and substance

### **Country of origin**

Norway

### **Launch**

2013

### **Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

[kvadrat.dk](http://kvadrat.dk)