



Savanna

Abrasion

Approx. 45.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 3, EN ISO 12945

Seam slippage

Seam parallel to warp: 2.5 mm parallel to weft: 6.5 mm
EN ISO 13 936-2 180 Newton

Snagging

Note 1-2 (Note 1-4, 1 best note) ICI Test method FAB 29, Tumble-Box

Lightfastness

Note 5-7 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12
Wet note 4-5 ISO 105-X12

Flame resistance

AS/NZS 3837 class 2
BS 5852 crib 5 with treatment *
BS 5852 part 1 with treatment *
EN 1021-1/2
NF D 60 013 with treatment *
SN 198 898 5.3 with treatment *
UNI 9175 11M with treatment *
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

** To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

Savanna

Design: Aggebo & Henriksen

Type: Upholstery

Composition: 34% polyester, 31% new wool, 26% polyacrylic, 4% cotton, 3% nylon, 2% linen

Yarn type: Spun

Binding: Dobby

Width: Approx. 140 cm, 55 inches

Weight: Approx. 681 g/lin.m, 22 oz/ly

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



ACT Guidelines Woven fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Colour Fastness to Light

Grade 5.0 minimum 40 hours

Physical properties

Pilling Class 3

Breaking Strength warp 161 / weft 200 lbs.

Seam Slippage warp 25 / weft 89 lbs.

Abrasion

45.000 cycles Martindale – High Traffic / Public Spaces

Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

Quality benefits

Very good abrasion

Very good lightfastness

Flame retardant

Green building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content
and substance

Country of origin

Norway

Launch

2013

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard
material is FSC certified and / or contains recycled content.

For further information
kvadrat.dk

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and
heavy metal restrictions

No content of PFCs or 'PFAS'

REACH compliant

Californian Proposition 65 list compliant

BC Red list compliant

California Prop 65 list compliant

kvadrat