



## Still

### Abrasion

Approx. 50.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

### Pilling

Note 4-5, EN ISO 12945

### Seam slippage

Seam parallel to warp: 3.0 mm parallel to weft: 2.0 mm  
EN ISO 13 936-2 180 Newton

### Lightfastness

Note 4-7 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 4-5 ISO 105-X12

### Absorption

0.60/Class C (flat), 0.85/Class B (waved) EN ISO 354

### Airflow

770 Pa s/m EN 29053

### Flame resistance

AS/NZS 3837 class 1  
ASTM E84 Class A Unadhered  
BS 5852 Crib 5  
BS 5852 part 1  
BS 5867 part 2 type B  
DIN 4102 B1  
EN 1021-1/2  
EN 13501-1, B-s1, d0  
GB 8624 B1  
IMO FTP Code 2010 Part 8  
NF D 60 013  
NF P 92 507 M1  
ÖNORM B1/Q1  
SN 198 898 5.2  
UNI 9175 IIM  
UNI 9177 Classe 1  
US Cal. Bull. 117-2013

### Still

Design: Georgina Wright

Type: Upholstery

*In accordance with California Bill AB 2998 and similar legislation within the United States, this product may not be used as upholstery. It can be used for vertical applications.*

Composition: 100% Trevira CS

Yarn type: Chenille

Binding: Satin

Width: Approx. 140 cm, 55 inches

Weight: Approx. 640 g/lin.m, 20.6 oz/ly

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week if fixed covers. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Also washable at 60-80°C, half wash load. Drip drying.

Mount in moist condition. Shrinkage app. 2% at 60°C.

Be aware of increased shrinking and creasing the higher the temperature.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk

60/

10 year  
warranty



# kvadrat

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking**

Dry Crocking: Grade 4.5

Wet Crocking: Grade 4.5

### **Colour Fastness to Light**

Grade 4.0 minimum 40 hours

### **Physical properties**

Pilling Class 4-5

Breaking Strength warp 308 / weft 140 lbs.

Seam Slippage warp 104.5 / weft 109 lbs.

### **Abrasion**

50.000 cycles Martindale – High Traffic / Public Spaces

### **Quality benefits**

Complies with Möbelfakta

Very good abrasion

Good lightfastness

Permanent flame retardant

Washable

### **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

No content of PFCs or 'PFAS'

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono-material designed for circularity

Recyclable

### **Green building certificates**

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): Based on a LCA following EN 15804 and follow the standard of ISO 14040

Health Product Declaration (HPD): Declaring textile content and substance

### **Country of origin**

Norway

### **Launch**

2019

### **Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

kvadrat.dk

# **kvadrat**