



Tampico II

Design: Kinnasand

Type: Curtain

Composition: 100% Trevira CS

Yarn type: Staple

Binding: Plain weave

Width: Approx. 298 cm, 117.5 inches

Weight: Approx. 235 g/lin.m, 7.5 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 30°C.

Drip drying.

Shrinkage approx. 1% / 0% when washed at 30°C.

Ironing might be necessary

Disinfection, see www.kvadrat.dk

More info: Care and maintenance [kvadrat.dk](http://www.kvadrat.dk)



10 year
warranty



Tampico II

Lightfastness

Note 4-7 ISO 105-B02

Flame resistance

AS/NZS 1530.3

ASTM E84 Class A Unadhered

CAN ULC S102

CAN ULC S109

DIN 4102 B1

EN 13 773 class 1

GB 8624 B1

IMO FTP Code 2010 Part 5

JIS L 1091 A-1 D

NF P 92 507 M1

NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4.5

Wet Crocking: Grade 4.5

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

Physical properties

Seam Slippage warp 58 / weft 61 lbs. ASTM D434

Quality benefits

Good lightfastness

Permanent flame retardant

Washable

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono material designed for circularity

Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Switzerland

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk

kvadrat