



Unix

Design: Kinnasand

Type: Curtain

Composition: 100% polyester FR

Yarn type: Filament, staple

Binding: Panama

Width: Approx. 153 cm, 60 inches

Weight: Approx. 420 g/lin.m, 13.6 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 1% / 0% when washed at 60°C.

Ironing might be necessary

Disinfection, see www.kvadrat.dk

More info: Care and maintenance [kvadrat.dk](http://www.kvadrat.dk)



10 year warranty



Unix

Lightfastness

Note 5-7 ISO 105-B02

Absorption

150 mm airgap

0.70/Class C (flat), EN ISO 354

100 mm airgap

0.50/Class D (flat), 0.75/Class C (waved) EN ISO 354

Airflow

597 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.2

AS/NZS 1530.3

BS 5867 part 2 type B

CAN ULC S102

CAN ULC S109

DIN 4102 B1

IMO FTP Code 2010 Part 5

IMO FTP Code 2010 Part 7

NF P 92 507 M1

NFPA 701

UNI 9177 Classe 1

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 4.5

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

Physical properties

Seam Slippage warp 10 / weft 23.5 lbs. (Fail) ASTM D434

Quality benefits

Good lightfastness

Permanent flame retardant

Washable

Acoustic performance

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono-material designed for circularity

Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Japan

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk