

Linex

Design: Kinnasand

Type: Curtain

Composition: 100% polyester FR

Yarn type: Filament Binding: Plain

Width: Approx. 150 cm, 59 inches Weight: Approx. 195 g/lin.m, 6.3 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 1% / 0% when washed at 60°C.

Ironing might be necessary
Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk







# Linex

## Lightfastness

Note 5-7 ISO 105-B02

#### Flame resistance

AS/NZS 1530.2 AS/NZS 1530.3 BS 5867 part 2 type B CAN ULC S102 CAN ULC S109 DIN 4102 B1 IMO FTP Code 2010 Part 5 NF P 92 507 M1 NFPA 701 SN 198 898 5.2 UNI 9177 Classe 1

## **ACT Guidelines Woven fabrics**

#### Flammability

NFPA 701

#### **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 5.0 Wet Crocking: Grade 5.0

## Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

## Physical properties

Seam Slippage warp 29 / weft 25.5 lbs. ASTM D434 Seam Slippage ASTM D434

## **Quality benefits**

Good lightfastness Permanent flame retardant Washable

# **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions
No use of halogen-based flame retardants (incl. brominated and chlorinated)
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Mono material designed for circularity
Recyclable



# **Green Building certificates**

Greenguard Gold: Low chemical emission Health Product Declaration (HPD): Declaring textile content and substance

# Country of origin

Japan

# Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information kvadrat.dk

