

Birches

Design: Kinnasand

Type: Curtain

Composition: 100% polyester FR

Yarn type: Filament

Binding: Dobby

Width: Approx. 149 cm, 58.5 inches

Weight: Approx. 210 g/lin.m, 6.8 oz/ly

Repeat: Approx. 63 cm, 25 inches V, 147 cm, 58 inches H

Colour difference may occur


Cleaning: Washing at max. 60°C. Drip drying.

Shrinkage approx. 1% when washed at 60°C.

Ironing might be necessary

More info: Care and maintenance kvadrat.dk

Disinfection, see www.kvadrat.dk



10 year
warranty



Birches

Lightfastness

Note 5-7 ISO 105-B02

Flame resistance

BS 5867 part 2 type B

CAN ULC S102

CAN ULC S109

DIN 4102 B1

NF P 92 507 M1

NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

Physical properties

Seam Slippage ASTM D434

Not required fabric under weight

Quality benefits

Good lightfastness

Permanent flame retardant

Washable

Benefits of Polyester FR

Polyester FR has hypoallergenic properties

Polyester FR dries fast

Polyester FR is inherently flame retardant, so no additional chemical treatment is needed

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono-material designed for circularity

Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): Based on a LCA following EN 15804 and follow the standards of ISO 14040

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Japan

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk